

<b>LCR750</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 3.4 ohm)
Frequency response	80-20Khz	(average response in room +/- 3dB )
Frequency roll off	80 Hz	(-6dB at 80 Hz near field )
Crossover frequency	1.6Khz	"Phase focused" (4th/2nd order)
Tweeter	1,1" Dome	Coated silk dome
Woofers	2 x 5.25"	Coated Glass Fibre
Power handling	150 watt	Long term IEC-268-5 (cycled input 80-20Khz)
Power handling	80 watt	Rated IEC-268-5 (constant input 80-20Khz)
Recommended amp power	25-200 watt	(Recommended amp power to drive speaker)
Sensitivity	90 dB	Average SPL 2.83V / 1mtr (on axis 200-10KHz)
System princip		Sealed enclosure
Connection	Terminal gold plating	Screw for 5 mm cable / Banana
Accessories	Yes	Mounting screw s/gloves/rubber feets
Welcome Card	Yes	"Included in packing"
Finish		Black Vinyl
Dimensions	H x W x D	16.1x7x8.8 inch - 40.8x17.8x22.3cm
Weight		15.25 lb / 6.9 kg
	Version 1. Feb 2019	