

<b>Surr 55T</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 4.2 ohm)
Frequency response	80-20Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	( -6dB at 80 Hz near field)
Crossover frequency	1.6Khz	"Phase focused" (4th&2nd order)
Front Tweeter	1,1" Dome	Coated silk dome
Front Woofer	5.25"	Coated Glass Fibre
Side drivers (shielded)	2 x 3.25"	Polymer coated Textured Paper
Power handling	100 watt	Long term IEC-268-5 (cycled input 87-20Khz)
Power handling	55 watt	Rated IEC-268-5 (constant input 87-20Khz)
Recommended amp power	25-150 watt	(Recommended amp power to drive speaker)
Sensitivity	85 dB	Average SPL 2.83V / 1mtr (on axis 200-10KHz)
System princip		Sealed enclosure
Connection	Terminal gold plating	Screw for 5 mm cable / Banana
Accessories	Yes	Wall mount brackets/screws/gloves/rubber feets
Welcome Card	Yes	"Included in packing"
Finish		Black Vinyl
Dimensions	H x W x D	10.2x7x8.7 inch - 25.9x17.8x22.1cm
Weight		10.25 lb / 4.7 kg
	Version 3. Nov 2012	